




HYBRID SOLAR INVERTER

PT11000-Max



FEATURE:

- **Touch LCD screen ,intuitive parameter display**
- **Novel and fashionable RGB atmosphere lights indicator**
- **Support parallel connection function, maximum 9 units**
- **Support three phase at parallel connection mode**
- **BMS communication , support lithium battery**
- **Dual Output & Dual PV Input**
- **Working with or without battery**
- **Support WiFi monitoring**



APPLICATION:



Camping



Home



Grassland



Mountain
Power



Island



Border
Post

PT11000-Max

-PARAMETERS-

PT11000-Max	
Phase	Single Phase
Nominal Voltage	220/230/240VAC
Voltage Range	90-280VAC±3V (Normal Mode) 170-280VAC±3V (UPS Mode)
Frequency Range	50Hz/60Hz(Adaptive)
OUTPUT	
Rated Power	11000W
PV Mode	12000W
Battery Mode/AC Mode	11000W
Output Voltage(AC)	220/230/240VAC±5%
Output Frequency	50/60Hz±0.1%
Dual Output Rated Power	Main Load: 11000W , Second Load : 11000W
Waveform	Pure Sine Wave
Transfer Time(Adjustable)	10ms for Computer , 20ms for Home Appliances
Peak Power	22000VA
Overload(Battery Mode)	105%~150% Load: 11s ; 150%~200% Load: 2s; >200% Load: 400ms
Peak Efficiency(Battery Mode)	>94%
GRID-TIE	
Output Voltage	220/230/240VAC
Feed-in Grid Voltage	170 - 264.5 VA
Feed-in Grid Frequency Range	49-51±1Hz/59-61±1Hz
Rated Feed-in Grid Current	47.8A
Peak Efficiency(DC/AC)	98%
BATTERY	
Battery Type	Lead-acid / Gel / Tubular /Lithium
Rated Voltage	48VDC
Constant Voltage Charging Voltage	56.4VDC (Adjustable)
Floating Charge Voltage	54VDC (Adjustable)
CHARGER	
PV Charging Method	Dual MPPT
PV Max Input Power	15000W (7500w+7500w)
MPPT Tracking Range	90~500 VDC
Best PV Voltage Range	360-430 VDC
Max PV Input Voltage	500 VDC
Max PV Input Current	27A+27A
Max PV Charging Current	150A
Max AC Charging Current	150A
COMMUNICATION PORT	
RS232	For External WiFi device / Monitoring & Update
RS485	For BMS Communication
Dry Connect	Support sending signal to start generator
Parallel Connection	Support maximum 9 units, Support three phase
ENVIRONMENTAL PARAMETERS	
Operating environment temperature	-10~50℃
Operating environment humidity	20%-95% (Non condensing)
Storage temperature	-15~60℃
Altitude	The altitude should not exceed 1000m, derating above 1000m, up to 4000m
Noise	≤50db
Certifications	IEC 62109-1, IEC 62109-2, IEC 61683